


Plunger Operated 2 Way Poppet Valve


42250



Material: Brass
Flow: 3 CFM @ 100 PSI
Dimensions: 1 3/4" L x 1/2" Hex.
Weight: 1 oz.
Mounting: Mounts in 5/16" hole




Plunger operated valve can be used to detect end of travel. Actuation force is pressure dependent and is approx. 1.1 lbs. at 90 PSI. Actuation stroke is between 1/64" and 1/16". Rear port accepts 1/8 ID tubing, secondary port is 10-32 (M5).



One Way Trip Mechanism

42300



One way trip mechanism can be used with plunger or ball operated valves. In one direction, mechanism forces ball to actuate valve. In the opposite traveling direction, mechanism is forced into base offering no resistance for valve switching. Tripping mechanism travel into base is 5/64". Overall dimensions: 1 1/8" L x 1/4" W x 3/8" H.


Air Bleed Hose and Nozzle

43138



Hose and nozzle accessory for Series 79, 81 and 72 air jet detector valves. Hose is 18" long, 5/32" OD tubing with push-in nozzle. A fitting is also included. Tubing can be cut to size.

Mounting Brackets



Flat Mounting Bracket **43010-1**
L Shaped Mounting Bracket **43010-2**

Dimensions:
Flat -1" H x 1 9/16" W.
L shape - 3/4" H. x 1 9/16" W x 3/8" D.
Mounting holes (2) 1/8" Dia. on 1 1/4" Centers.

Used to mount mechanically operated valves with screw thread mounting collar and nut. Made from zinc plated sheet steel. Valve mounting hole is 1/2 inch diameter.

Miniature Valves

Accessories

(Manual and Mechanically Operated Valves)

Kuhnke Miniature Valves

Miniature OT Pushbutton Operators

Kuhnke series 46, 74, 79 and 81 valves can be used with *Moeller* type M22 oil tight pushbuttons. See *individual types for valve catalog numbers*. Operators are used on control panels to enable pneumatic valves to be mounted along with electromechanical devices. Operators are standard miniature size (7/8" dia. mounting hole). For selection and descriptions of pushbuttons visit www.moeller.net. To order operators, contact *Moeller* directly. Following are typical actuator catalog numbers;

Description	Moeller Type	Moeller Article No.
Momentary Pushbutton	M22-D-S	216590
Two position Selector	M22-S-WR	216856
Mushroom Head Pushbutton	M22-DP-S	216712
Latching Pushbutton	M22-PV	216876
Key Lock	M22-WRS	216887

Replacement Operators

2 Way Roller Lever	MM4930017
One Way Roller Lever	MM4930016
Cat Whisker (79/81)	MM4920003